

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Aviation oil

TWA (TLV): 200 mg/l

STEL (TLV):NA

SAO-4

Flammable Range:

Specification:

	Extended	Standard	Extended
Measurement Range	Do not extend	0.1 – 5 mg/l	Do not extend
No. of Pump Strokes		1 (100 mL)	
Volume Correction Factor (VCF)*		1.0	
Sampling Time	1 minute per pump stroke (100 mL)		
Color Change	White → Brown with green top		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	Aviation oil + I ₂ O ₅ + H ₂ SO ₇ → I ₂		
Relative standard deviation	± 10 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
H ₂ S	60	+	Light brown
Hexane	25	+	
Octane	5	+	
Gasoline	25	+	
Benzene	25	No	No Effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0812