

# Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

## Ethyl Formate $C_3H_6O_2$

## SEF-4M

TWA (TLV): 100 ppm

STEL (TLV): NA

Flammable Range: 2.8 – 16 %

### Specification:

Measurement Range	Extended	Standard	Extended
	Do not extend	20 – 500 ppm	Do not extend
No. of Pump Strokes	2 (200 mL)		
Volume Correction Factor (VCF)*	1.0		
Sampling Time	3.0 minutes per pump stroke		
Color Change	Yellow → Pale Green		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	$C_3H_6O_2 + Cr^{6+} + H_2SO_4 \rightarrow Cr^{3+}$		
Relative standard deviation	± 10 %		

\* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

### Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Alcohols		+	Yellow to Pale green
Esters		+	Yellow to Pale green
Ketones		+	Yellow to Pale green
Aromatic Hydrocarbons		+	Yellow to Pale green

### Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



**Manufactured By:** Uniphos Envirotronic Pvt. Ltd.  
Nahuli (PO), Umbergaon (Tal.)  
Valsad (Dist), Gujarat, India – 396108

Rev.0812