

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Ethylene Oxide C_2H_4O

SEO-7

TWA (TLV): 1 ppm

STEL (TLV): NA

Flammable Range: 4-100%

Specification:

Measurement Range	Extended	Standard	Extended
	0.025-1.5%	0.05-3.0%	0.1-6.0%
No. of Pump Strokes	2 (200 mL)	1 (100 mL)	0.5 (50 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2.0
Sampling Time	2.0 minutes per pump stroke		
Color Change	Orange → Brownish Green		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	$C_2H_4O + Cr^{6+} + H_2SO_4 \rightarrow Cr^{3+}$		
Relative standard deviation	± 10 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Alcohols		+	Orange to Brownish Green
Esters		+	Orange to Brownish Green
Ketones		+	Orange to Brownish Green
Aromatic Hydrocarbons		+	Orange to Brownish Green

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0812