

# Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

## Hydrogen Sulfide H<sub>2</sub>S

TWA (TLV): 1 ppm

STEL (TLV): 5 ppm

## SHS-3L

Flammable Range: 4-44%

### Specification:

	Extended	Standard	Extended
Measurement Range	1.25-30 ppm	2.5-60 ppm	5-120 ppm
No. of Pump Strokes	2 (200 mL)	1 (100 mL)	0.5 (50 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2.0
Sampling Time	1.5 minutes per pump stroke		
Color Change	White → Brown		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	H <sub>2</sub> S + Pb(CH <sub>3</sub> COO) <sub>2</sub> → PbS + 2CH <sub>3</sub> COOH		
Relative standard deviation	± 10 %		

\* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

### Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Mercaptans	100	No	No effect
SO <sub>2</sub>	100	No	No effect

### Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



**Manufactured By:** Uniphos Envirotronic Pvt. Ltd.  
Nahuli (PO), Umbergaon (Tal.)  
Valsad (Dist), Gujarat, India – 396108

Rev.0812