

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Hydrogen Sulfide H₂S

TWA (TLV): 1 ppm

STEL (TLV): 5 ppm

SHS-5M

Flammable Range: 4-44%

Specification:

	Extended	Standard	Extended
Measurement Range	50-1000 ppm	100-2000 ppm	200-4000 ppm
No. of Pump Strokes	2 (200 mL)	1 (100 mL)	0.5 (50 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2.0
Sampling Time	1.5 minutes per pump stroke (100 mL)		
Color Change	White → Brown		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	H ₂ S + Pb(CH ₃ COO) ₂ → PbS + 2CH ₃ COOH		
Relative standard deviation	± 10 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Mercaptans	500	No	No effect
NO ₂	200	No	No effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0812