

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Methanol

TWA (TLV): 200 ppm

CH₃OH

STEL (TLV): 250 ppm

SME-5

Flammable Range: 6-36.5%

Specification:

Measurement Range	Extended	Standard	Extended
	Do not extend	100 – 5000 ppm	Do not extend
No. of Pump Strokes		1 (100 mL)	
Volume Correction Factor (VCF)*		1	
Sampling Time	1.5 minutes per pump stroke (100mL)		
Color Change	Yellow → Light green		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	CH ₃ OH + Cr ⁶⁺ + H ₂ SO ₄ → Cr ³⁺		
Relative standard deviation	± 10 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Alcohols		+	Yellow to Light green
CO ₂	10 %	No	No Effect
CO	1000	No	No Effect
SO ₂		No	No Effect
Acetone	1%	No	No Effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0812