

# Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

## Sulphur Dioxide SO<sub>2</sub>

TWA (TLV): 2 ppm

STEL (TLV): 5 ppm

## SSD-7M

Flammable Range: NA

### Specification:

	Extended	Standard	Extended
Measurement Range	0.05 - 1.5 %	0.1 - 3 %	0.2 - 6%
No. of Pump Strokes	2 (200 mL)	1 (100 mL)	0.5 (50 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2.0
Sampling Time	1 minute per pump stroke (100 mL)		
Color Change	Yellow → Green		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	SO <sub>2</sub> + Cr <sup>6+</sup> + H <sub>2</sub> SO <sub>4</sub> → Cr <sup>3+</sup>		
Relative standard deviation	± 10 %		

\* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

### Possible Interferences:

Compound	Concentration (%)	Interference	Colour change / Comments
H <sub>2</sub> S		+	Slight ring
CO		+	Slight colour change
CO <sub>2</sub>	3	No	No Effect

### Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



**Manufactured By:** Uniphos Envirotronic Pvt. Ltd.  
Nahuli (PO), Umbergaon (Tal.)  
Valsad (Dist), Gujarat, India – 396108

Rev.0812