

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Water Vapor

H₂O

SWA-5

TWA (TLV): NA

STEL (TLV): NA

Non Flammable

Specification:

	Extended	Standard	Extended
Measurement Range	Do not extend	0.1– 2 mg/l	Do not extend
No. of Pump Strokes		1 (100 mL)	
Volume Correction Factor (VCF)*		1.0	
Sampling Time	1 minute per pump stroke (100 mL)		
Color Change	Yellow → Greenish blue		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F).		
Reaction Principle	H ₂ O + Mg (ClO ₄) ₂ → Mg(ClO ₄) ₂ .H ₂ O		
Relative standard deviation	± 10 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
CH ₄	99.9%	No	No effect
H ₂ S	2000	No	No effect
Methanol	50	No	No effect
Hexane	3000	No	No effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
-------------	--



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0812