

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Ethyl Mercaptan in LPG C₂H₅SH SEM-(3M)

TWA (TLV): 0.5 ppm

STEL (TLV): NA

Flammable Range: 3-18%

Specification:

	Extended	Standard	Extended
Measurement Range		2 - 80 ppm	
No. of Pump Strokes		1 (100 mL)	
Volume Correction Factor (VCF)*		1.0	
Sampling Time	35 seconds per pump stroke (100 mL)		
Color Change	Yellow → Pink		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	C ₂ H ₅ SH + HgCl ₂ → C ₂ H ₅ S.HgCl + HCl HCl + Base → Chloride		
Relative standard deviation	± 10 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Other Mercaptan		+	Yellow to Pink
PH ₃		+	Yellow to Pink
H ₂ S		+	Yellow to Pink
Arsine		+	Yellow to Pink
HCN		+	Yellow to Pink

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0713