

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Water Vapor

H₂O

SWA-4

TWA (TLV): NA

STEL (TLV): NA

Non Flammable

Specification:

Measurement Range	Extended	Standard	Extended
	3-20 lb/MMCF	6-40 lb/MMCF	12-80 lb/MMCF
No. of Pump Strokes	2 (200 mL)	1 (100 mL)	0.5 (50 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2.0
Sampling Time	1.5 minutes per pump stroke (100 mL)		
Color Change	Yellow → Dark green		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F).		
Reaction Principle	$H_2O + Mg(ClO_4)_2 \rightarrow Mg(ClO_4)_2 \cdot H_2O$		
Relative standard deviation	± 10 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
CH ₄	99.9%	No effect	No effect
H ₂ S	2000	No effect	No effect
Methanol	50	+	Yellow to light green

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
-------------	--



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0217